

**Gusher®
Urchin**



Model	On Deck Fixed Handle	Thru Deck Bulkhead	On Deck Removable Handle
Product Code	BP9005	BP9013	BP9021
Weight	0.6 kg (1.3lb)	0.96 kg (2lb)	0.7 kg (1.5lb)
Hose Connections	25 mm (1") or 38 mm (1 ½") Smooth Hose Connections		
Materials	Pump Body: Glass-filled Polypropylene, Clamp Ring: Acetal Diaphragm: Neophrane (Nitrile option available) Operating Lever (BP9021 only): Glass-filled Nylon Handle, Springs, Fasteners: Stainless Steel		
Materials In Contact With Fluid	Glass-filled Polypropylene, Nitrile, Neophrane, Stainless Steel		
Maximum Suction Lift	4 m (13.5 ft)		
Maximum Discharge Head	3 m (10 ft)		
25mm (1") Hose connection - Suitable as a primary bilge pump on boats up to 12m (40ft) in accordance with ISO150831 38mm (1½") Hose connection - Suitable as a primary bilge pump on boats equal to or greater than 12m (40ft) in accordance with ISO150831.			

Compact Bilge and Waste Water Transfer Pump

- Compact design is ideal for confined spaces
- Smooth easy action up to 55 ltrs (14.5 US gals) per minute
- Clamp ring easily removed for pump head rotation and quick maintenance
- Three different mounting orientations (deck, bulkhead and thru deck models)
- Dual size nozzles for 25 mm (1") or 38 mm (1½") hose

Performance Data	BP9005/BP9013/BP9021	BP9005/BP9013/BP9021
25 mm (1") Hose		
Suction Lift	1 m (3 ft)	2 m (6 ft)
Discharge Head	0.5 m (1.5 ft)	0.5 m (1.5 ft)
45 Strokes per Minute	25 ltrs (7 US gals)	25 ltrs (7 US gals)
70 Strokes per Minute	43 ltrs (11.4 US gals)	40 ltrs (10.6 US gals)
38 mm (1 ½") Hose		
Suction Lift	1 m (3 ft)	2 m (6 ft)
Discharge Head	0.5 m (1.5 ft)	0.5 m (1.5 ft)
45 Strokes per Minute	37.5 ltrs (9.9 US gals)	36 ltrs (9.5 US gals)
70 Strokes per Minute	55 ltrs (14.5 US gals)	53 ltrs (14 US gals)