



## Safety Data Sheet

Product name :

CERAN WR 2

Page : 1/6

SDS n° :31521-44

Version :1.00

Version of :2004-09-28

This sheet supersedes the one dated :2004-06-16

### PRODUCT LABELS

LABELLING (standard or EU):

Not concerned

R-phrases :

None

S-phrases :

None

TRANSPORT LABELLING:

Not applicable.

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY UNDERTAKING

Name of the product :

CERAN WR 2

Code No. :

H52

Product application :

Lubricating grease

Supplier :

TOTAL UK LIMITED  
40 Clarendon Road  
Watford, Hertfordshire, WD17 1TQ  
UNITED KINGDOM  
Tel: 01923 694000  
Fax: 01923 694400

\*Contact :

Specific Product Related Info: 01977 636200

\*Emergency telephones :

UK - 01923 694000

\*Poisons Advice Centre :

NHS Direct: 0845 46 47 / Textphone: 0845 606 46 47

\*Burns Units :

NHS Direct: 0845 46 47 / Textphone: 0845 606 46 47

See local details at end of sheet :

Manufacturer :

TOTAL UK LIMITED  
40 Clarendon Road  
Watford, Hertfordshire, WD17 1TQ  
UNITED KINGDOM  
Tel: 01923 694000  
Fax: 01923 694400

### 2. HAZARDS IDENTIFICATION

\*Health effects :

Under normal conditions of use, the product holds no danger of intoxication

Environmental impact :

Do not discharge this product into the environment.

Physico-chemical hazards :

No specific risk of fire or explosion under normal conditions of use

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### PREPARATION

Chemical nature :

The product is made from refined mineral base oils and synthetic oils in which the polycyclic aromatic hydrocarbons (PCA or P14) content, measured by IP 346, is less than 3%.

Substances presenting a health hazard	EC No.	CAS No.	Content	Symbol(s)	R-phrases
Alkylated diphenylamines	270-128-1	68411-46-1	<1 %	N	R-51/53

See section 16 for explanations of R-phrases :

## Safety Data Sheet

**Product name :**

**CERAN WR 2**

Page : 2/6

SDS n° :31521-44

Version :1.00

Version of :2004-09-28

This sheet supersedes the one dated :2004-06-16

### 4. FIRST AID MEASURES

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Inhalation :	Inhalation of heavy concentrations of vapour, fumes or spray, may cause mild irritation of the throat. Transport the person into fresh air, keep warm and allow to rest.
Ingestion :	Possible risk of vomiting and diarrhoea. Do not induce vomiting to avoid the risk of aspiration into the respiratory tract.
Skin contact :	Immediately remove all soiled or stained clothing. Wash the affected area immediately and repeatedly with soap and water. If the skin is exposed to high-pressure spray, the product may enter the human body. In all such cases the affected person must be taken to hospital, even if no sign of injury can be detected.
Eye contact :	Keep eyes open and rinse immediately and repeatedly with water for at least 15 minutes.

### 5. FIRE FIGHTING MEASURES

Flash point:  
See heading 9

Extinguishing media :  
- suitable:  
Foam, carbon dioxide (CO<sub>2</sub>), powder.  
- not recommended:  
do not use water jets (stick jets) for extinguishing fire since they could help to spread the flames.

Specific hazards :  
Incomplete combustion and thermolysis produce gases of varying toxicity such as CO, CO<sub>2</sub>, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled.

Protective measures for firefighters :  
Insulated breathing apparatus must be worn in confined premises with heavy concentrations of fumes and gases.

Other :  
All combustion residues and contaminated water from fire-fighting should be disposed of according to local regulations.

### 6. ACCIDENTAL RELEASE MEASURES

See sections 8 and 13.

Personal protection :  
Ensure good ventilation.  
Remove sources of ignition. Do not smoke.

After spillage / leakage :  
- On the soil:  
Surfaces on which the product has been spilled may become slippery.  
Do not allow the product to enter sewers or rivers or contaminate the soil.  
Recover with mechanical means such as pumps and skimmers.  
Contain and collect the spilled product with sand or any other inert absorbant material.  
In case of spillage, contact the competent authorities if the situation cannot be brought under control rapidly and efficiently.  
- On water:  
Floating absorbant material, then mechanical recovery.  
If the product is spilled in a river or in the sewers, notify the authorities of the possible presence of surface effluent.

## Safety Data Sheet

**Product name :**

**CERAN WR 2**

Page : 3/6

SDS n° :31521-44

Version :1.00

Version of :2004-09-28

This sheet supersedes the one dated :2004-06-16

### 7. HANDLING AND STORAGE

#### HANDLING :

Prevention of user exposure :

Ventilate extensively if the formation of vapours, fumes, mists or aerosol is a risk.  
Make all the necessary arrangements in order to reduce exposure risk, notably to products in use or to wastes.

Keep away from combustible substances; keep away from food and beverages.

Prevention of fire and explosion :

Empty containers may contain flammable or explosive vapours.  
There is a fire hazard associated with rags, paper or any other material used to remove spills which become soaked with product.  
Avoid accumulation of these: they are to be disposed off safely after use.

Precautions :

Avoid static electricity build up with connection to earth.  
Set up machinery and equipment so as to avoid the risk of accidental spills or splashes onto hot machine parts and electrical contacts (on joint failure, for example).

#### STORAGE :

Technical measures :

Make the necessary arrangements to prevent water and soil pollution.

Storage precautions :

- Suitable:  
Store at room temperature, protected against contact with water and moisture, and away from any source of ignition.  
Keep containers closed when not in use  
- To be avoided:  
Do not store exposed to the elements.

Incompatible products :

Dangerous reaction with strong oxidizing agents.

Packaging materials :

- Recommended:  
Use only hydrocarbon-resistant containers, joints, pipes, etc.  
Keep in original container if possible.  
Otherwise, transfer all indications on the regulatory label to the new container.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Technical measures :

Use the product in a properly ventilated atmosphere.  
When working on enclosed place (tanks, reservoirs...), make sure that atmosphere is not suffocating and/or wear recommended equipment.

Respiratory protection :

It is not necessary in normal conditions.  
In case of vapours or sprays formation:  
Combined gas cartridge (organic gases and dust, filter A/P2).

Hand protection :

Impermeable hydrocarbon-proof gloves.  
recommended material: nitrile , neoprene.  
The demands on the gloves are determined by the conditions in practice (e.g. multiple use, mechanical load, temperature, strength and duration of exposition).  
Before choosing suitable gloves, it is recommended that the user tests the gloves.  
The break through times of the same type of glove of different manufacturers can be very different - even if the layer thickness is similar. Therefore the break through times have to be found out from the manufacturer of the protective gloves themselves.

Eye protection :

Goggles, in case of risk of splashing.

Skin and body (other than the hands) protection :

As required, wear a face mask, hydrocarbon-proof clothing, and safety boots (when handling drums).  
Don't wear rings, watches or anything similar which can retain the product and may give rise to skin conditions.

## Safety Data Sheet

**Product name :**

**CERAN WR 2**

Page : 4/6

SDS n° :31521-44

Version :1.00

Version of :2004-09-28

This sheet supersedes the one dated :2004-06-16

Hygienic work practices :

Avoid prolonged and repeated contact with the skin, especially with used or waste product  
Immediately remove all soiled or stained clothing.  
If the product comes into contact with the skin, wash the affected area immediately and copiously with soap and water.  
Do not use abrasives, solvents or fuels.  
Do not use cloths stained with the product to dry hands.  
Do not put the product-soaked rags into the pockets of working clothes.  
Do not eat, drink or smoke while handling the product.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance :

Pasty

Colour :

Brown.

Odour :

Characteristic

Density/specific gravity :

900 kg/m3  
Temperature (°C) 15

Température d'auto-inflammation :

> 300 ° C (ASTM E 659)

Comments on autoignition temperature :

This temperature may be significantly lower under particular conditions (slow oxidation on finely divided materials...).

Comments on explosivity :

Not applicable  
Drop point: > 290 ° C

Solubility :

- in water :  
Insoluble and immiscible.  
- in organic solvents :  
Soluble in many common solvents.

### 10. STABILITY AND REACTIVITY

Stability :

The product is stable at normal storage, handling and use temperatures.

Conditions to avoid :

Heat, sparks, ignition points, flames, static electricity.

Materials to avoid :

Avoid contact with strong oxidizers

Hazardous decomp. products :

Incomplete combustion and thermolysis produces potentially toxic gases such as CO, CO<sub>2</sub>, various hydrocarbons, aldehydes and soot.

### 11. TOXICOLOGICAL INFORMATION

Acute toxicity / Local effect :

Inhalation, comments:

Risk is improbable under normal conditions of use  
Inhalation of high concentrations of vapour or aerosols may cause irritation of the upper respiratory tract.

Skin contact, comments:

Risk is improbable under normal conditions of use.  
If the skin is exposed to high-pressure spray, the product may enter the body. In all such cases the affected person must be taken to hospital, even if no sign of injury can be detected

Ingestion, comments:

In case of ingestion of small quantities, no important effect observed. in case of ingestion of larger amounts: abdominal pain, diarrhea, ...

#### CHRONIC TOXICITY OR LONG-TERM TOXICITY :

Skin contact :

Characteristic skin affections (oil blisters) may develop following prolonged and repeated exposure through contact with stained clothing

## Safety Data Sheet

<b>Product name :</b>	<b>CERAN WR 2</b>	Page : 5/6
SDS n° :31521-44	Version :1.00	Version of :2004-09-28
This sheet supersedes the one dated :2004-06-16		

Sensitization :	To our knowledge, the product does not cause aggravated sensitivity.
-----------------	--

### 12. ECOLOGICAL INFORMATION

Comments about ecotoxicity :	Experimental data on the finished product are not available. It is considered to present a little danger for aquatic life. no information available for used product
Mobility :	- Air: there is a slow loss by evaporation. - Soil: Given its physical and chemical characteristics, the product has no soil mobility. - Water: The product is insoluble; it spreads on the surface of the water
Persistence and degradability :	No experimental information about the finished product. However the "mineral oil" fraction of the new product is intrinsically biodegradable.

### 13. DISPOSAL CONSIDERATIONS

Waste disposal :	Dispose of in a safe manner, in accordance with local regulations. If need be, collection by an authorised waste contractor and regeneration or incineration at an approved installation.
Waste class :	The waste classification mentioned here represents only a recommendation. The waste producer is responsible for the correct specification of the waste. The specification of the waste classification should be in arrangement with the authorised waste disposal company. The waste classification is dependant on the composition of the product at the time of disposal. 12 01 12
Disposal of contaminated packaging :	Proceed in compliance with the prevailing regulations.

### 14. TRANSPORT INFORMATION

UN N°: not applicable	
Road (ADR) / Rail (RID) :	
Class :	Not restricted for transport.
Transport by barge (ADNR) :	
Marine (IMO-IMDG) :	
Air (ICAO/IATA) :	

### 15. REGULATORY INFORMATION

Not applicable	
Risk phrases :	None
Safety phrases :	None
EU directives :	Hazardous preparations directive 1999/45/EC modified (Directive 2001/60/EC).
INVENTORIES:	
CANADA (DSL) :	All components on DSL, NDSL
EUROPE (EINECS) :	All components on EINECS inventory



## Safety Data Sheet

**Product name :**

**CERAN WR 2**

Page : 6/6

SDS n° :31521-44

Version :1.00

Version of :2004-09-28

This sheet supersedes the one dated :2004-06-16

JAPAN (ENCS) :

All components on ENCS

PHILIPPINES (PICCS) :

All components on PICCS

USA (TSCA) :

All components listed in TSCA

AUSTRALIAN (AICS) :

All components on AICS

KOREA (ECL) :

All components on ECL

CHINA :

All components on IECSC

### 16. OTHER INFORMATION

Explanations of R-phrases in section 2 :

R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

\*Revision date:

2004-09-28

\*Supersedes the data sheet of:

2004-06-16

\* Information revised since the previous version of the SDS :

SDS No. :

LT-DS-1002

Safety Data Sheet status :

Approved.