

Hose	: IMPERMEABLE SANITARY 'NO SMELL' HOSE
Application	: Hoses are to be used for transportation of biological waste, e.g. in combination with toilet installations on yachts and small craft. Excellent physical and performance characteristics. Not suitable for potable water.
Lining	: Biological waste, toilet cleaning chemicals and salt water resistant, BLACK , SBR rubber.
Reinforcement	: Woven synthetic fabric and steel helix wire embedded between the layers.
Cover	: Salt water resistant, WHITE, SBR / EPDM rubber.
Temperature	: Suitable for use in the range - 40 to + 70° Celsius.
Relevant CE Standards	: ISO 8099
Classification	: Non

Code	I.D.		O.D.	Steel Wire		Working Pressure		Burst Pressure		Bending Radius		Force	Weight	
				Diam.	Pitch									
	mm	inch	mm	mm	mm	bar	psi	bar	psi	mm	inch	N	kg/m	lbs/ft
SAHOSE16	16	5/8	26	1.0	8	3.0	43.5	10	145	50	2	2.0	0.45	0.30
SAHOSE19	19	3/4	29	1.0	8	3.0	43.5	10	145	65	2 1/2	2.0	0.55	0.37
SAHOSE25	25	1	36	1.0	8	3.0	43.5	10	145	75	3	3.0	0.72	0.48
SAHOSE38	38	1 1/2	48	1.5	10	3.0	43.5	10	145	100	4	3.5	1.15	0.74
SAHOSE51	51	2	62	1.5	6	3.0	43.5	10	145	125	5	5.0	1.54	3.40
SAHOSE102	102	4	115	2.0	6	3.0	43.5	10	145	250	10	10.0	3.86	2.59

Odour test acc. to test method US005442952A: 95 ppm
Test sample SAHOSE38

Identification:	
0.5 mtr	vetus® Sanitary hose 25 mm
Blue ribbon over full length of hose 0.5 meter Mark, Hose type and dimension repeated every 0.5 meter	